

SUPERFAST CONCRETE-STICK

Product Description

Superfast Concrete-Stick Epoxy Putty is a fast-setting polymer compound that enables permanent repairs to concrete and masonry. It also bonds to metals, wood, glass and many plastics.

Each handy stick contains pre-measured portions of activator and base throughout – no measuring or mixing tools are necessary. As the epoxy is mixed, the two contrasting colours blend into one colour to indicate complete mixing. The consistency eliminates drips and runs, facilitates adhesion to the substrate, and allows the material to be shaped and formed as needed before curing begins. Once cured, Superfast Concrete-Stick can be tapped, drilled, sawed, filed or painted, and will have an appearance and texture similar to concrete.



Suitable for interior or exterior use, it is resistant to water, chemicals, and temperature extremes. Superfast Concrete-Stick contains no solvents or VOC's. It's non-flammable and releases no noxious fumes. It won't shrink or pull away. The unused portion stays fresh for future use when saved in its original package.

Superfast Concrete-Stick has a work life of approximately 4 minutes. Within 5-10 minutes it will harden and form a cohesive bond. After 1 hour, the system can be put back into service.

Performance Data*

MINIMUM SHELF LIFE (months @ 24°C.)	24
HARDNESS, SHORE D (full cure, 24 hrs.)	80
LAP SHEAR TENSILE STRENGTH (MPa)	
On Steel	4.1
On Concrete	Concrete Failure
COMPRESSIVE STRENGTH (MPa)	83
DENSITY (gm/cm ³ , lb/gal)	2.0, 16.7
SHRINKAGE (%)	<1
NON-VOLATILE CONTENT (%)	100
ELECTRICAL RESISTANCE (megohms)	30,000
DIELECTRIC STRENGTH (volts/mil)	300
UPPER TEMPERATURE LIMIT	
Continuous (°C)	120
Intermittent (°C)	150
CHEMICAL RESISTANCE	
Resistant to hydrocarbons, ketones, alcohols, esters, halocarbons, aqueous salt solutions and dilute acids and bases.	

*Typical properties: for information only; not for specification purposes.